


# GRILLI ZINCATI A OMEGA

Con perno a vite - Serie Americana




Codice	Carico massimo di utilizzo kg	Dimensioni principali mm					
		D	H	B	C	S	D1
GPV00330	330	6	10	22	16	5	12
GPV00500	500	9	12	28	20	6	17
GPV00750	750	9	13,5	30	21	9	21
GPV01000	1000	11	18	34	26	10	25
GPV01500	1500	12,5	17	43	28	11	26
GPV02000	2000	15,5	20	46	32	13	31
GPV03250	3250	18	25	62	42	16	40
GPV04750	4750	21	30	69	49	20	48
GPV06500	6500	25	34	82	56	23	53
GPV08500	8500	29	42	96	66	25	59
GPV09500	9500	32	43	108	72	29	67
GPV12000	12000	35	48	120	78	33	75
GPV13500	13500	38	53	135	90	36	84
GPV17000	17000	41	62	147	98	41	95
GPV25000	25000	51	76	175	123	46	108
GPV35000	35000	55	80	195	147	52	129
GPV55000	55000	72	111	265	185	64	144

Coefficiente di sicurezza 6:1

Conforme alla Direttiva Macchine 2006/42/CE

# GRILLI ZINCATI A OMEGA

Con dado a coppiglia - Serie Americana



Codice	Carico massimo di utilizzo kg	Dimensioni principali mm					
		D	H	B	C	S	D1
GDC002000	2000	15	19	47	32	13	30
GDC003250	3250	18	26	62	42	16	40
GDC004750	4750	21	31	70	49	19	48
GDC006500	6500	24	36	84	56	23	52
GDC008500	8500	27	43	96	66	25	59
GDC009500	9500	32	45	108	72	29	67
GDC012000	12000	35	50	120	80	32	73
GDC013500	13500	39	61	135	93	35	84
GDC017000	17000	42	64	147	98	41	95
GDC025000	25000	51	77	180	128	44	110
GDC035000	35000	55	92	195	145	52	129
GDC055000	55000	72	111	265	185	64	144
GDC085000	85000	80	127	330	190	75	165
GDC120000	120000	95	146	381	238	89	203
GDC150000	150000	108	165	400	275	102	230

Coefficiente di sicurezza 6:1

Conforme alla Direttiva Macchine 2006/42/CE